











| | | | | | | | | |
|--|---|---|--|---|---|---|---|---|
| Product description | A60 E27 220-240V 6W 470LM NON-DIM 2700K 260° 15000HRS, Seoul LED | A60 E27 220-240V 9W 806LM NON-DIM 2700K 260°15000HRS, Seoul LED | A60 E27 220-240V 9.5W 806LM DIM 2700K 260° 15000HRS,Seoul LED | A60 E27 220-240V 10.5W 1055LM NON-DIM 2700K 200° 15000HRS,Seoul LED | GU10 220-240V 3.3W 250LM NON-DIM 2700K 36° 15000HRS,Seoul LED | B35 E14 220-240V 3W 250LM NON-DIM 2700K 240° 15000HRS, Seoul LED | P45 E27 220-240V 3.3W 250LM NON-DIM 2700K 240° 15000HRS, Seoul LED | P45 220-240V 3.3W 180LM NON-DIM 2300K 15000HRS, Seoul LED |
| Type | 1102271199 | 1102271207 | 1102271215 | 1102271258 | 1102022030 | 1102140432 | 1102150622 | 1102150948 |
| Barcode (For Kruidvat) | 4894532454020 | 4894532454068 | 4894532454167 | 4894532454174 | 4894532453672 | 4894532453702 | 4894532453993 | 4894532453528 |
| Norminal life time of the lamp (hours) | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 |
| Number of switching cycles | ≥30000 | ≥30000 | ≥30000 | ≥30000 | ≥30000 | ≥30000 | ≥30000 | ≥30000 |
| Colour temperature (K) | 2700 | 2700 | 2700 | 2700 | 2700 | 2700 | 2700 | 2300 |
| Warm-up time up to 60% of the full light ouput 60% | Instant full light | Instant full light | Instant full light | Instant full light | Instant full light | Instant full light | Instant full light | Instant full light |
| A warning if the lamp cannot be dimmed or can be dimmed only on specific dimmers | non-dimmable | non-dimmable | dimmable | non-dimmable | non-dimmable | non-dimmable | non-dimmable | non-dimmable |
| Lamp dimensions (Length & Diameter) | 61.5*108mm | 61.5*108mm | 61.5*108mm | 61.5*108mm | 54*50mm | 98*35mm | 76*45mm | 76*45mm |
| Equivalence incandescent lamp power(w) | 40W | 60W | 60W | 75W | 38W | 25W | 25W | 18W |
| Rated luminous flux(lm) | 470LM | 806LM | 806LM | 1055LM | 250lm | 250lm | 250lm | 180lm |
| Rated lamp life time(hours) | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 | 15000 |
| Rated power(w) | 6W | 9W | 9.5W | 10.5W | 3.3W | 3W | 3.3W | 3.3W |
| Lamp power factor | >0.5 | >0.5 | >0.5 | >0.5 | >0.4 | >0.4 | >0.4 | >0.4 |
| Lumen maintenance factor at the end of the nominal life(%) | 70% | 70% | 70% | 70% | 70% | 70% | 70% | 70% |
| Starting time (s) | <0.5S | <0.5S | <0.5S | <0.5S | <0.5S | <0.5S | <0.5S | <0.5S |
| Color rendering | ≥80 | ≥80 | ≥80 | ≥80 | ≥80 | ≥80 | ≥80 | ≥80 |
| Nominal beam angle (degrees) | N/A | N/A | N/A | N/A | 36° | N/A | N/A | N/A |
| Colour consistency | <6 | <6 | <6 | <6 | <6 | <6 | <6 | <6 |
| Rated peak intensity in candela (cd) | N/A | N/A | N/A | N/A | 700 | N/A | N/A | N/A |
| Spectral power distribution in the range 180-800 nm |  |  |  |  |  |  |  |  |
| Input current(mA) | 50mA | 73mA | 48mA | 85mA | 28mA | 26mA | 26mA | 26mA |